



**CÔNG TY TNHH LỘC HOÀ DẦU NGHĨ SƠN**  
 NGHI SƠN REFINERY AND PETROCHEMICAL LLC

**MSRP**  
**list of equipment/ spare parts**

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
1	2083100179	Salvage Sheet	SALVAGE SHEET, STANDARD 6 X 6 & 12 X 12FT, HEAVY GRADE SALVAGE SHEETS SUITABLE FOR MORE RUGGED PURPOSES, READY TO USE EYELETS ARE SPACED AT ONE METRE INTERVALS IN THE REINFORCED HEMS AND ALL FOUR CORNER EYELETS ARE REINFORCED BY A CORNER PATCH, UV PROTECTED, ROTPROOF, FLEXIBLE AND EASY TO HANDLE, 100% WATERPROOF, 100% ROTPROOF, AVAILABLE IN A RANGE OF COLORS	Vanguard	8	Pc
2	2050654060	Push Lock of fire hose cabinet	PUSH LOCK, FOR HOSE CABINET, CAM: 68MM LG X 31MM WD, LOCK 8.6MM LG, 2.6CM WD, 1.4CM THK, LOCK RED BUTTON A240-3, MATERIAL: MILD STEEL, FINISHING: ZINC PLATING	Common	100	Pc
3	2049952672	Fire Hose cabinet	CABINET, HOSE CABINET, 900 W X 1400 H X 600 MM D, 1.5MM THK, TYPE -1A, EG MILD STEEL, DRAIN HOLD, M10 X 4HOLDS, VENTILATION: LEFT & RIGHT PANELS, ROOF: SLOPING, FINISHING: EPOXY POWDER COATED, RED RAL 3020, COMPLETED SET OF HOSE CABINET FOR HYDRANT	Common	20	Set
4	2040154082	Landing valve 1.5"	HYDRANT VALVE, OBLIQUEUE TYPE, RF GLANGE 2" ANSI 150#, FEMALE INSTANTANEOUS 1.5IN X 1.5IN BSP, 3.3KG, LANDING VALVE 1.5", 2" OBLQ LDG VLV WITH 38MM F.INST OUTLET, HYD067-GM-38BSPCAP ADPTOR 1-1/2" FBS336XF 1-1/2" BSP GM W CAP, COMMERCIAL QUOTATIONHYC087-GM-038-CW CAP GM 1-1/2" M.BS336 C/W SS CHAIN&HOOK, WITHOUT FLANGE COVER, MANUF SRI	SRI	10	Pc



**CÔNG TY TNHH LỘC HOÁ DẦU NGHĨ SƠN**  
 NGHI SƠN REFINERY AND PETROCHEMICAL LLC

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
5	2080200828	Cable tie	CABLE TIE, STAINLESS STEEL CABLE TIE, 250MM X 5MM, POCKET 50PCS	Common	20	Poc
6	2083100175	Face shield	FACESHIELD, PART# HP-EFSNG4, 4X150IN, NEW GENERATION FOR HONEYWELL LITE FORCE HELMETS, MANUF HONEYWELL	HONEYWELL	20	Pc
7	2083100526	Fire extinguisher sign	SIGN, FIRE EXTINGUISHER SIGN, SIZE: 200MM X 200MM, JALITE PRODUCTS IS CLASSIFIED UNDER ISO 17398 C CLASS & IS THIRD PARTY TESTED TO CONFORM TO THE REQUIREMENTS OF IBC CODE 2009 SECTION 10.24 & NEW YORK CITY CODE	Common	100	Pc
8	2003100150	Flexible Hose (Inox 304 - Model: FL-110)	HOSE, FLEXIBLE, 8IN, 150#, 5000MM L, INOX 304, 1.6 MPA, ASME B16.5, MODEL: FL-110	Common	1	RLL
9	2083100935	9Kg fire extinguisher cabinet	CABINET, 9KG FIRE EXTINGUISHER CABINET, 280MM (W) X 690MM (H) X 250 MM (D), 1.5MM THK, MATERIAL: MILD STEEL, DRAIN HOLD, M10 X 4HOLDS, VENTILATION: LEFT & RIGHT PANELS, ROOF: SLOPING, FINISHING: EPOXY POWDER COATED, RED RAL 3020	Common	20	Pc
10	2030558520	Ball valve 1/4"	VALVE, BALL VALVE WITH LEVER, 0.25IN DIA, BODY MATERIAL CARBON STEEL A216 WCB, BALL MATERIAL STAINLESS STEEL A351 -CF8M, BONNET MATERIAL CARBON STEEL A216 WCB, LEVER MATERIAL STAINLESS STEEL 304, ASSEMBLY TYPE FEMALE BSP THREADED ENDS, MAX WORKING PRESSURE 6.3 MPa, ANTIN BLOW OUT STERM, LOCKING DEVICE, FULL BORE	Common	2	Pc



NSRP

**CÔNG TY TNHH LỌC HOÁ DẦU NGHĨ SƠN**

NGHI SƠN REFINERY AND PETROCHEMICAL LLC

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
11	2030558521	Check valve 6200 series	VALVE, CHECK VALVE, 6200 SERIES, MAX WORKING PRESSURE: 20.7MPa, SS316, MANUF HOKE, CV FACTOR 2,4, CRACKING PRESSURE 0,0137 Mpa, ASSEMBLY TYPE FEMALE 1/2 IN NPT THREADED ENDS	HOKE	2	Pc
12	2040656807	Pressure regulator	REGULATOR, PRESSURE REGULATOR, MODEL RB 2500, AI GROUP, BODY MATERIAL ALUMINIUM, ASSEMBLING PARTS MATERIAL CARBON STEEL, INTERNAL PARTS MATERIAL STAINLESS STEEL / BRASS, GAZ INLET CONNECTION FEMALE 3/4 IN BSP, GAZ OUTLET CONNECTION FEMALE 3/8 IN BSP, PILOTING GAZ INLET FEMALE 3/8 IN BSP, SET PRESSURE 1 MPa	AI GROUP	2	Set
13	2030558522	Pressure safety valve	VALVE, SAFETY VALVE, MODEL 381, BODY MATERIAL BRONZE CC491 K, AUTERXIER, DISC MATERIAL FPM, INLET CONNECTION MALE 1 IN BSP, OUTLET CONNECTION FEMALE 1 IN BSP, MAXIMUM WORKING PRESSURE 4 Mpa, SET PRESSURE 1,2 Mpa, WORKING TEMPERATURE (MIN/MAX) -196°C / 225°C	AUTERXIER	2	Set
14	2040656808	Filter	FILTER, TEE TYPE FILTER, BODY MATERIAL STAINLESS STEEL 316, CONNECTION MALE 1/4 IN NPT, MAX WORKING PRESSURE 41,3 Mpa, NOMINAL PORE SIZE 7 µM, MODEL TF SERIES, MANUF SWAGelok	GENERIC	2	Set
15	2050710108	Powder nozzle	NOZZLE, POWDER NOZZLE, MATL ALUMINIUM, FLOW: 300KG/MIN, MODEL 2981, CODE 9982, POK, INLET CONNECTION SYMMETRICAL COUPLING DSP40, ORIFICE DIAMETER 25 MM, RANGE 10 M	POK	2	Pc
16	2020900038	Pressure gauge	GAUGE, TANK PRESSURE GAUGE, SCALE 0-1 ,6 MPA, DIAMETER 100MM, MODEL 233.5, CONNECTION G 1/2 IN, WIKA, BODY MATERIAL STAINLESS STEEL, GLASS MATERIAL LAMINATED SAFETY GLASS, WETTED PART MATERIAL STAINLESS STEEL 316LM	Common	2	Pc



NSRP

**CÔNG TY TNHH LỌC HOÁ DẦU NGHĨ SƠN**  
 NGHI SƠN REFINERY AND PETROCHEMICAL LLC

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
17	2040154146	Continuous flow hose reel	HOSE REEL, CONTINUOUS FLOW HOSE REEL AND STAND 1000 X 800 X 650MM, WORKING 700KPA, MATERIAL SS304, EPOXY POWDER COATED, RED RAL 3020, HOSE SIZE: 1.5IN, SS304 STAND, INCLUDE 0.375IN X 3IN LENGTH ZINC PLATED SLEEVE ANCHOR, BOLT AND NUTS M10 X 80	Common	20	Set
18	2040154145	Hose of Indoor hose reel	HOSE REEL, HOSE OF INDOOR HOSE REEL, HOSE TYPE COLLAPSIBLE (FLAT), DIA 40MM, LENGTH 30M, WEIGHT 8KG, MAX SERVICE PRESSURE 1.6MPa, TEST PRESSURE 2.4MPa, INLET CONNECTION 1.5 IN (DN 40) FEMALE, OUTLET CONNECTION 1.5 IN (DN 40) MALE	SRI	20	Rll
19	2040154078	Hose of outdoor hose reel	HOSE, 1.5IN DIA, 40M LG, BLACK, MAX PRESSURE 700KPA, TEST PRESSURE 1400KPA, BURST PRES 2500KPA, PVC, NORMALLY FLOW LITRER/MIN: 250LPM @ 700KPA REFERENCE: VV215Z-002-A-109_8_0010, PVC	SRI	20	RLL
20	2040154080	Ball Valve	VALVE, BALL VALVE, BRASS 1-1/2IN CH - 1.5IN DIA, BRASS/ CHROME	Common	5	Pc
21	2083100936	Tarpaulin for foam discharge test	TARPAULIN, COLOR GREY, PVC, 0.38MM, 12MX13M, TEMPERATURE RESISTANCE -30°C-+70°C	Common	1	PC
22	2083100937	Tarpaulin for foam discharge test	TARPAULIN, COLOR GREY, PVC, 0.38MM, 8MX10M, TEMPERATURE RESISTANCE -30°C-+70°C	Common	1	PC
23	2083100186	SCBA air quality test tube	GAS DETECTION TUBE, PART# 6728371, TUBE OIL MIST 10/a-P, MEASURING RANGE 0.1 TO 1 MG/M3, 10 TUBE/BOX, MANUF DRAGER	Drager	6	Box
24	2083101010	SCBA air quality test tube	GAS DETECTION TUBE, PART# 6728511, CARBON MONOXIDE 5/a-P, MEASURING RANGE 5 TO 150 PPM, 10 TUBE/BOX, MANUF DRAGER	Drager	6	Box
25	2083100184	SCBA air quality test tube	GAS DETECTION TUBE, PART# 6728521, CARBON DIOXIDE 100/a-P, MEASURING RANGE 100 TO 3000 PPM, 10 TUBE/BOX, DRAGER	Drager	6	Box



NSRP

**CÔNG TY TNHH LỘC HOÀ DẦU NGHĨ SƠN**  
 NGHI SƠN REFINERY AND PETROCHEMICAL LLC

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
26	2083100185	SCBA air quality test tube	GAS DETECTION TUBE, PART# 8103061, WATER VAPOR 20/a-P, MEASURING RANGE 20 TO 1500 MG H2O/M3, 10 TUBE/BOX, MANUF DRAGER	Drager	6	Box
27	2003100126	Stand support for fire extinguisher cabinet	SUPPORT, STAND SUPPORT FOR FIRE EXTINGUISHER CABINET, SS 304, DIMENSION: 2.5IN x 350 x 3MM, COLOR: RED	Common	60	Pc
28	2030861578	Gasket for landing valve	GASKET, RUBBER, 2.5IN DIA, 1.6MM THK, RUBBER Z40, FOR LANDING VALVE Z40 G6 DRS098 IN HYD052-CS-3WY-JC (VV215Z-002-A-102), MANUF SRI	SRI/ Equivalent	150	Pc
29	2050256219	Washer for landing valve	WASHER, RUBBER, FOR LANDING VALVE, 2.5IN DIA, G6, RUBBER Z40 - G6 RUBBER WASHER FOR 65MM OBLIQUE TYPE HYDRANT VALVE, ORSOG6-RB-XXX-BK, MANUF SRI	SRI/ Equivalent	100	Pc
30	2050454223	Grease nipple 10mm	GREASE NIPPLE, THREAD SIZE: 10MM/1/8BSP, GOLD TONE, 18MM LG, 11MM DIA (0.7IN LG, 0.43IN DIA), GREASE NIPPLE 10MM, HRP372-SS-006-NA NIPPLE GREASE SS 6MM-CONT, HR SS304, FOR MONITOR FOS007, MANUF SRI	SRI/ Equivalent	200	Pc
31	2060144493	Nozzle for fixed monitor	NOZZLE, MONITOR, FLOW RATE 2000LPM, PRESSURE: 700KPA, STRAIGHT STREAM, FEMALE THREAD 2.5IN, L290, H200, WITH HANDLE CAP RUBBER, DEFLECTOR G.M, INLET BODY G.M, COVER C.M MANUF: 202222	SRI/ Equivalent	10	Set
32	2049952675	Foam branch pipe of Fire hose box	PIPE, BRANCH PIPE FOAM LOW EXP, C/W 450 OF FIRE HOSE BOX, PART#: FOS008-LA-450-YW, MANUF: SRI	SRI/ Equivalent	15	Pc
33	2040154077	Grease nipple 6mm	HOSE REEL, NIPPLE GREASE, 6MM, M.S/Z. PLATE, NIPPLE GREASE MS ZP 6MM-CONT, HR FOR CONTINUOUS FLOW HOSE REEL HRS059-MS-038-SV, HRP372-MS-006-ZP, MANUF SRI	SRI/ Equivalent	200	Pc



NSRP

**CÔNG TY TNHH LỘC HOÁ DẦU NGHĨ SƠN**  
 NGHI SƠN REFINERY AND PETROCHEMICAL LLC

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
34	2030558512	Pressure reducing valve for outdoor hose reel	VALVE, PRESSURE REDUCING VALVE, BRASS, INLET UP TO 2000KPA/OUTLET 100KPA-700KPA, 60DEG C, 1.6 KG, VALVE HR PRESS REDUCING GM 50MM NAHRS063-GM-050-NA, MANUF SRI	SRI/ Equivalent	30	Pc
35	2040154079	Nozzle for outdoor hose reel	NOZZLE, 1.5IN DIA, TEST PRESSURE 1400KPA, INLET 1.5IN BSP ALLUMINIUM ALLOY, P/N WRS099-LA-038-NA	SRI/ Equivalent	15	Pc
36	2263100094	Spanner to operate the valve for emergency case	SPANNER, 42-64MM, 800MM L, FOR EMERGENCY CASE, AÆ 25MM C-SHAPED WRENCH MOUTH: 42 – 64MM, THE ANGULAR HOOK AND CONCAVE GRIPPING SURFACE ENSURE RELIABLE CONTROL OVER THE WRENCH AND THE HANDWHEEL. MATERIAL: STAINLESS STEEL	Common	10	Pc
37	2263100095	Spanner to operate the valve for emergency case	SPANNER 600 MM L, MAT: SS, FOR EMERGENCY CASE, AÆ 25MM - C-SHAPED WRENCH MOUTH: 34 – 54MM, THE ANGULAR HOOK AND CONCAVE GRIPPING SURFACE ENSURE RELIABLE CONTROL OVER THE WRENCH AND THE HANDWHEEL	Common	10	Pc
38	2263100096	Stand rack for Spanner	RACK, STAND RACK FOR SPANNER, 300 X 300 X 1000 MM, MAT: CAPACITY 02 SPANNERS, RED COLOR PAINT, PLATE BASE: 300 X 300MM WITH 4-HOLES AÆ 10MM TO CATCH THE BOLT AND NUTS, NOTICE SIGN ""FOR EMERGENCY USE ONLY"" DIA 200X200MM WELDED ON THE RACK BODY, 02 HOLES FOR HOLDS THE SPANNER AÆ 35MM WELDED ON THE BODY, MATERIAL: STAINLESS STEEL	Common	10	Pc
39	2263100100	Flexible Hose (Inox 304 - Model: FL-110)	HOSE, FLEXIBLE, 6IN, 150#, 4000MM L, INOX 304, 1.6 MPA, ASME B16.5, MODEL: FL-110	Common	3	RLL
40	2263100102	Flexible Hose (Inox 304 - Model: FL-110)	HOSE, FLEXIBLE, 3IN, 150#, 8000MM L, INOX 304, 1.6 MPA, ASME B16.5, MODEL: FL-110	Common	3	RLL



NSRP

**CÔNG TY TNHH LỘC HOÁ DẦU NGHĨ SƠN**  
NGHI SƠN REFINERY AND PETROCHEMICAL LLC

No	Maximo code	Description/ Commodity	Specification	Brand	Estimated quantity	UOM
41	2263100093	Metal Stairs to operated the valve	LADDER, METAL STAIRS TO OPERATED THE VALVE, DIA: 1000 X 600 X 1881MM, MATERIAL: STAINLESS STEEL, SQUARE STAINLESS-STEEL TUBE 30 X 30 X 2.6MM, STAINLESS STEEL PLATE 600 X 200 X 2.6MM, RUBBER-LINED SOLE BASE	Common	3	Pc
42	2263100103	Fire Extinguisher weigh scale	SCALE, BATTERY POWERED SCALE, CAPACITY: 45KG X 0.01KG, DIMENSIONS: 278MM X 318MM X 56MM, MODEL: DWS2/ GP100USB, BATTERY POWERED DIGITAL WEIGHING SCALES FOR USE DURING FIRE EXTINGUISHER SERVICING, BATTERY POWERED ELECTRONIC PORTABLE SCALE, KG/LB UNIT SWITCHING, AUTO SHUT-OFF TO MAXIMISE BATTERY LIFE, BLUE LCD BACKLIGHT DISPLAY, MANUF SALTER BRECKNELL DIGITAL SCALES	Common	2	Set